H 296
DETAIL F
SCALE 18"=1'-0"
SECTION B-B
SECTION C-C
VIEW F-F
SCALE 1"=1'-0"
DETAIL E
SCALE 12"=1'-0"
VIEW A-A
SECTION D-D
SECTION E-E
SCALE 18"=1'-0"
SECTION H-H
SCALE 18"=1'-0"
NOTE: GUARD SHOULD BE PRESSED TIGHT AGAINST STRINGER TO PREVENT RATTLING
NOTE: 28E2101 -FOR -0 ASSY. 28E2101-100 -FOR -100 ASSY. 28E2101-150 -FOR -150 ASSY. 28E2101-800 -FOR -800 ASSY. MAKE SIMILAR CHANGES FOR ALL PARTS REFLECTED ON THE RESPECTIVE ASSYS.
28F2297-23 & -28 SWING TO SUPPORT DOOR IN HORIZONTAL POSITION
DOOR SWING OPEN TO HORIZONTAL POSITION
ELEC. CONDUIT OF 28E2101 (REF) CONNECT CONDUIT & COMPLETE WIRING AS PER 28E2101. THIS LOCATION FOR PBY-4 ONLY
PERCOLATOR CAC® PE-1 8 CUP CAPACITY. IF PE-1 IS NOT AVAILABLE, CAC® PE-25 (10-14 CUP CAPACITY) MAY BE USED
ELECT. POWER UNIT INST. 28E-P025 (REF)
NOTE: CAC® PE-1 MAY BE PURCHASED FROM AMERICAN WHOLESALE HARDWARE CO., LOS ANGELES, CALIF. VENDOR'S CAT. #3272. CAC® PE-25 MAY BE PURCHASED FROM THE BELLAIRE ENAMEL CO., BELLAIRE OHIO
MISC. & FOOD LOCKERS SAME AS 28F1055 (REF)
NOTE: VOL. OF FOOD LOCKER = 3.7 CU.FT. (APPR.)
NOTE: LOCATION OF STRAP ON 28B950-7 (REF) TO SUIT 28E2101 (REF) IN STOWED POSITION
BASELINE (REF)
CONSOLIDATED AIRCRAFT CORP.
INSTALLATION-FURN STOVE & FOOD LOCKER
J 28F2246
ENG. FILE

28F2246 R